

FC-Z



DELIVER CONSISTENT FLAVOR

COMPENSATE FOR SHOT PREP VARIATIONS WITH PATENTED TECHNOLOGY ENGINEERED TO ENSURE EACH SHOT IS PERFECTION

OPTIMIZE BARISTA WORKFLOW AND MAINTAIN QUALITY

WITH EASY-TO-USE, REPEATABLE EXTRACTION PROGRAMS, NOW EACH OF YOUR BARISTAS CAN DELIVER THE IDEAL SHOT OF ESPRESSO REGARDLESS OF VOLUME OR SKILL

DRIVE CUSTOMER LOYALTY

WITH CONSISTENCY THAT WILL DELIGHT BOTH CUSTOMERS AND BARISTAS, YOU CAN QUICKLY BUILD YOUR REPUTATION & SALES

MAINTAIN CONSISTENT FLAVOR

— USING —

SMART-PUMP™ TECHNOLOGY

FLOW IS CONTROLLED IN REAL-TIME COMPENSATING FOR CHANGES IN GRIND, TAMP & DOSE SIZE



CREATE THE PERFECT SHOT

WITH -

7 CONTROL PARAMETERS

THEN SAVE AND REPLICATE

VISIBLE PUMPS & PULLEYS MAKE EVERY SHOT A SHOW

LEARN MORE AT DUVALLESPRESSO.COM

TOUCHSCREEN INTERFACE FEATURES

EXTRACTION DASHBOARD

CONFIGURE YOUR SHOT PARAMETERS, THEN WATCH YOUR EXTRACTION RUN IN REAL-TIME ON OUR INTERACTIVE PERFORMANCE FEEDBACK GRAPH

7 CONTROL PARAMETERS

- 1. TEMPERATURE | 0-98°C
- 2. VOLUME DISPENSED | 10-400 CC
- **3. INFUSION TIME** | 5-999 SEC
- 4. PRE-INFUSION PRESSURE | 0 9 BAR
- **5. PRE-INFUSION FILL RATE** | 1-20 CC/SEC
- **6. DWELL TIME** | 0-99 SEC
- 7. FLOW RAMP M | -1 TO 1

RECENT EXTRACTIONS

A LOG OF THE RECENT SHOTS RUN SO YOU CAN EXPERIMENT AND HONE YOUR FLAVOR

DATABASE

STORE 100+ UNIQUE EXTRACTION PROGRAMS AND RUN INSTANTLY

USER PERMISSIONS





561.666.8289 | DUVALLESPRESSO.COM



SPECIFICATIONS	2 GROUP	3 GROUP
Height:	18 "	18″
Width:	33"	42.8"
Depth:	26.7"	26.7"
Weight:	250 lbs	320 lbs
Voltage (VAC, Φ, Hz):	208-240, 1, 60	208-240, 1, 60
Total Wattage* (240 VAC): Steam Element Coffee Boiler Group Head	7500 3000 2 x 1700 2 x 300	9500 3000 3 x 1700 3 x 300
Steam Boiler Capacity:	7.2 L	8.5 L
Coffee Boiler Capacity:	2 x 3L	3 x 3 L
Saturated Group Capacity:	2 x 0.1 L	3 x 0.1 L

^{*}Low wattage versions also available.